



TECHNICAL DATA SHEET

Rigid

2512

DESCRIPTION/ APPLICATION

2512 is a rigid extrusion PVC compound for interior applications. This compound is part of a family of products that partially contains a recycled stream, which helps to make end products more cost-competitive. This product is white and typically used in end products that are non-color or non-appearance critical.

GENERAL PROPERTIES	VALUE	METHOD
Specific Gravity (+/- 0.02)	1.44	ASTM D-792

MECHANICAL PROPERTIES	VALUE	METHOD
Tensile Yield Strength, psi	6,500	ASTM D-638
Tensile Modulus, psi	475,000	ASTM D-638
Tensile Impact, ft-lbs/in ²	45.5	ASTM D-1822
Tensile Elongation, %	2.6	ASTM D-638
1/8" Notched Izod Impact	3.0 ft-lbs/in	ASTM D-256
1/4" Notched Izod Impact	2.2 ft-lbs/in	ASTM D-256

Revision Date: 9/29/2015

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein shall be construed as a license to operate under, or recommendation to infringe, any patents.